



WATER HEATERS WITH HEAT EXCHANGER (T) FOR VERTICAL MOUNTING ON THE WALL						
CHARACTERISTICS						
Model	...	72268(H)T	72270(H)T	72266(H)T	72280(H)T	72281(H)T
Rated volume	L	80	100	120	150	200
Rated pressure	MPa	0,8	0,8	0,8	0,8	0,8
Rated voltage	V	220-230~	220-230~	220-230~	220-230~	220-230~
Rated electrical power	W	2 (3)	2 (3)	2 (3)	2 (3)	2 (3)
Maximum D.H.W. tank temperature in	°C	75	75	75	75	75
Heat exchanger surface area	m ²	0.36	0.41	0.53	0.59	0.59
Heat exchanger inside volume	L	1.31	2.01	2.58	2.87	2.87
Heat exchanger surface area (H)	m ²	0.48	0.56	0.66	0.84	0.84
Heat exchanger inside volume (H)	L	2.51	4.4	5.24	6.6	6.6
Weight when empty	kg	33 (24.5(H))	38 (28,5 (H))	44 (33 (H))	56.5 (46.5(H))	69.5 (59(H))
CONNECTIONS						
1: Hot water outlet		G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M
2: Cold water inlet - Drain		G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M
3: Temperature indicator		-	-	-	-	-
4: Control panel		-	-	-	-	-
5: Flange with heating element		-	-	-	-	-
6: Heating coil - Feed		G1/2 M	G3/4 F	G3/4 F	G3/4 F	G3/4 F
7: Heating coil - Return		G1/2 M	G3/4 F	G3/4 F	G3/4 F	G3/4 F
8: Socket for thermostat (Only for 72280(H)T and 72281(H)T)		-	-	-	G1/2 F	G1/2 F
DIMENSIONS						
A	mm	1065	1000	1165	1015	1255
B	mm	980	915	1080	930	1170
C	mm	145	175	175	190	190
D	mm	385	460	460	586	586
E	mm	80	96	96	105	105
F	mm	400	474	474	600	600
G	mm	32	32	32	43	43
I	mm	380	345	365	270	370
J	mm	450	385	450	450	450
M	mm	-	-	-	560	780

Symbol:
H - stainless steel tank